

ARSV Laurence M. Gould

Principal Features and Technical Information

General		
Vessel Owner	Offshore Vessel Services LLC	
Address	Galliano, Louisiana	
Builder	North American Shipbuilding, U.S.A.	
Year of Construction	1997	
Chartered for	Lockheed Martin ASC	
Address	Centennial, Colorado	
Classification	Ice Class ABS A1	
Flag	U.S.A.	
Principal Dimensions		
Length Overall	230 ft	70.2 m
Length Between Perpendiculars	212 ft	64.7 m
Breadth (molded)	46 ft	14.02 m
Breadth (with ice reamers)	56 ft	17.1 m
Draft	18 ft	5.49 m
Depth	25.75 ft	7.85 m
Lightship Weight	2755 LT	2799 t
Deadweight	1025 LT	1041 t
Loadline Displacement	3780 LT	3841 t
Gross Tonnage	2966 (international)	
Loadline Displacement	3780 LT	3841 t
Main Propulsion Machinery		
Shafts		
Number of Shafts	2	
Total Shaft Horsepower		
Open Water	4576 HP	
Ice Operations	3900 HP	
Main Engines		
Number of Engines	2	
Manufacturer	Caterpillar	
Model	3606	
Propellers		
Variable Pitch in Kort Nozzles		
Number	2	
Diameter	8.6 ft	2.65 m
Rudders		
High Lift	2	
Generators		
Number	3	
Rating	700 kW	
Manufacturer	Caterpillar	
Model	3508	
Emergency Diesel Generator		
Number	1	
Rating	500kW	
Manufacturer Model	Caterpillar	3408
Cruising Range	12,000 miles	
Endurance	75 days	
Tank Capacities		
Fuel	245,400 gallons	
Fresh Water	37,385 gallons	
Sewage and Wash water	12,142 gallons	
Ballast	322,218 gallons	
Accommodations		
Crew	16	
Scientist and Staff	28	
Berthing Van Capacity	9	
Total	53	
Over-The-Side Handling Equipment		
Cranes		
Main Crane	13.5 ton	60 ft reach
Aft Knuckle Crane	3.5 ton	20 ft reach
Forward Auxiliary Crane	1/2 ton	

ARSV Laurence M. Gould

Principal Features and Technical Information

A-frames			CTD Fish	Sea-Bird	SBE 9+
Stern A-frame	10 metric tons	7.5 m clearance	CTD Pressure Sensor	Paroscientific	410K-105
Starboard A-frame	5 metric tons		Dissolved Oxygen	Sea-Bird	SBE 43
Baltic A-frame	5 metric tons		CTD Pump	Sea-Bird	SBE 5
Winches			CTD Pump	Sea-Bird	5T
DUSH 5 Hydrographic Winch (Baltic Room)	10,000 m of 0.322 in. electro mechanical cable		Fluorometer	Wet Labs	FLRTD
DUSH 4 Winch (2 Interchangeable Drums)	One drum carries 9,000 m of 1/4 in. wire	One drum carries 6,000 m of 0.322 in. conducting wire	PAR	Biospherical Instruments	QSP-200L4S
DUSH 11 Winch (Interchangeable Drums)	One drum carries 7,300 m of 9/16 in. torque balanced mechanical wire	One drum carries 5,000 m of 0.680 in. coaxial cable	PAR	Biospherical Instruments	QSP-2300
Deck Tugger Winch	3/8 in. mechanical wire		Temperature	Sea-Bird	3-02/F
Deck Utility Winch	1/4 in. mechanical wire		Temperature	Sea-Bird	3plus, 6,800 m
Mooring Winch	Interchangeable between vessels		Transmissometer	WET Labs	C-Star
Streamer Winch	Interchangeable between vessels		XBT (auto launcher) / XCTD	Sippican MK-21	
Water-Column-Sampling Equipment			Diving Equipment		
Blake Trawl	5 ft		Dive Compressors (1 on board)	Bauer	Fills to 3,000 psi
Otter Trawls (2)	18 ft	30 ft	Dive Van (for storage/setup of dive equipment)	20 x 8 x 8.5 ft	
Isaac Kidd Midwater Trawl	1 m		DAN (Divers Alert Network) Oxygen Kit		
Flat Trawl	35 ft		Water Purification Equipment		
MOCNESS	1 m	10 m	E-pure Four Holder System	Barnstead	Type I water quality (ultrapure), 2L/minute
Tucker Trawl, opening/closing	3 nets		Reverse Osmosis & De-ionized (DI) Water System	Aqua Solutions Aqua-1 Compact	Type II water quality (analytical grade DI)
Optical Plankton Counter			Underway Seawater System		
Conductivity Temperature Depth (CTD) Sensors			Description:		
Description:			The seawater system supplies seawater to the Aquarium Room, Wet Lab and Hydro Lab. Green strand piping, a non-metallic, chemically resistant material, has been used throughout the system to minimize algae and bacterial growth. It also maintains its structural integrity under low temperatures. Large diameter piping and a minimum of 90° turns helps to prevent the formation of frazil ice in the system. The seawater system is also equipped with a centrifugal ice-strainer/de-bubbler.		
The Sea-Bird 911+ offers real-time operation via sea cable telemetry, includes a solid state memory module, and has a maximum depth of 6800 m. The CTD is mounted on a 24-bottle General Oceanics rosette. Five, 12, and 30L bottles available.			Three Intakes		
Altimeter	Benthos	PSA-916	Main	At Skeg	
Conductivity	Sea-Bird	4M (6,800m)	Secondary	At Moon Pool	3 ft above keel
Conductivity	Sea-Bird	4-02/O	Tertiary (used mainly for removing ice)	At Moon Pool	below water line
Conductivity	Sea-Bird	4C			

ARSV Laurence M. Gould

Principal Features and Technical Information

Surface Seawater Sampling Equipment			Meteorological Sensor Suite		
Fluorometer	WET Labs	FLRTD	Humidity/Wet Temperature	RM Young	41372LC
Micro Thermosalinograph	Sea-Bird	45	Anemometer	Gill	Wind Observer II Ultra-sonic
Transmissometer	WET Labs	C-Star 25 cm	Barometer	RM Young	61201
pCO ₂ Equilibration System	Lamont-Doherty Earth Observatory		PIR (pyrgeometer)	Eppley	PIR
Aquaria and Deck Incubators			PSP (pyranometer)	Eppley	PSP
Aquaria	6 Fiberglass	1000L Xactic Tanks	PAR Radiometer	Biospherical Instruments	QSR-240/P
Deck Incubator	3 Plexiglas	UV Transparent	PUV (underwater)	Biospherical Instruments	PUV-2500
Bottom-Sampling Equipment			GUV (mast)	Biospherical Instruments	GUV-2511
Dredges			Time & Navigation System		
Deep-Sea Rock Dredge	Scripps Institute of Oceanography		Position, Attitude, Heading GPS	SeaPath	330
Small Chain Dredge, Rock Dredge	Kahl Scientific		Time & Frequency Standard	Symmetricom	XLi
Large Chain Dredge, Rock Dredge	Kahl Scientific		GPS	Garmin	GA29
Coring Equipment			Communication Equipment		
Description: The vessel can be equipped with several coring devices for vertical sediment sampling.			The LMG is Global Maritime Distress Safety System (GMDSS) compliant. This means that there is automatic and complete redundancy for each mode of communication for ship to ship and ship to shore.		
Box Corer	Ocean Instruments		Fleet Broadband	Thrane and Thrane	FBB500
Jumbo Piston Corer	Woods Hole Oceanographic Institute		Inmarsat-B	NERA Saturn-B HSD	
Grab Sampler	Smith-MacIntyre		Inmarsat-C	Sailor	
Gravity Corer			Iridium	Motorola	9505a
Kasten Corer	State University of New York/Ocean Instruments		VHF		
Mega Corer	Mark I		Sailor	RT146	Bridge to Bridge
Standard Piston Corer	Woods Hole Oceanographic Institute		Sailor	RT2048	Main
Sonar Systems			Sailor	RM2042	Watch Receiver
Acoustic Doppler Current Profiler (ADCP)	RD Industries	150 kHz Narrow Band VM-150	VHF H/H		
3.5 kHz Sub-Bottom Profiler	Knudsen	3260 Chirp, 10 KW	Sailor	SP300	
12 kHz Bottom Tracker	Knudsen	3260 Chirp, 10 KW	Sailor	T2130	
Chirp Sidescan Sonar / Sub-Bottom Profiler, towed	Teledyne Benthos	SIS-1625, max. depth: 2000 m			
Sidescan Sonar / Sub-Bottom Profiler	Teledyne Benthos	SIS-1625			
12 kHz Sonar Receiver	Raytheon PDR	for pinger tracking			
Pinger 12 kHz	OIS	6000 (6,000 m)			

ARSV Laurence M. Gould

Principal Features and Technical Information

Computers and Networking		NOTES	
Description: Support Windows, Macintosh and Linux operating systems. There are usually four to six computers available for general use in the E-Lab and in the 01 Lounge.			
Network	200 LAN drops throughout the ship, including cabins		
E-mail			
Transmitted every 30 minutes via satellite.			
Size Restrictions:	10 MB incoming and outgoing		
Space Allocation			
Scientific Laboratory Spaces			
Wet Lab	425 sq. ft		
Hydro Lab	526 sq. ft		
Dry Lab	356 sq. ft		
Electronics/ Computer Lab	460 sq. ft		
Aquarium Room	270 sq. ft		
Environmental Room	48 sq. ft		
Microscope Room	25 sq. ft		
Science Workshop	380 sq. ft		
Changing (Mud) Room	58 sq. ft		
Baltic Room/Scientific Changing Room	427 sq. ft		
Exterior Main Deck			
Deck tie down points are located at 2 ft centers on the main deck			
Lower Deck			
Scientific Storage	Four 20 ft containers		
Science Vans			
Radioisotope Vans	2 vans	20 x 8 x 8 ft	
Freezer Lab	2 vans	20 x 8 x 8 ft	
Garage/Trace Metal Clean Lab	1 van	20 x 8 x 8 ft	
Recreation / Leisure Spaces			
Lounge / Library	670 sq. ft		
Gymnasium	196 sq. ft		
Sauna / Jacuzzi	144 sq. ft		